

GK250

STEEL EXHAUST AIR GRILLE



VARIANTS

GK250

The grille type GK250 is used for air exhaust in facilities such as offices, workshops, warehouses, shopping centres,... The grille can be used for wall or duct mounting. Execution in steel, standard finish painted white (RAL9010).

Steel wall grille with fixed stamp-formed horizontal blades with 45° deflection

Free passage ca. 40%

TECHNICAL INFORMATION

APPLICATION	Type	Exhaust
	Direction	Horizontal, fixed stamp-formed blades, déflection 45°
CONSTRUCTION	Center distance between blades	8,5mm
	Thickness of frame	8mm
	Min. length	100mm
	Max. length	750mm
	Available steps in length	50mm
	Min. height	100mm
	Max. height	550mm
	Available steps in height	50mm
MATERIAL	Standard material	Painted steel
	Standard finishing	Powder coating RAL9010
	Product finishing options	Powder coating RAL of choice
MOUNTING	Mounting options	Screw fixing

QUICK SELECTION

Exhaust Q _v [m³/h]		L [mm]					
H [mm]	L _w	200	300	400	500	600	750
200	25 dB(A)	96	144	195	243	294	368
	35 dB(A)	142	205	271	333	397	491
300	25 dB(A)	-	218	294	368	444	556
	35 dB(A)	-	300	397	491	586	726
400	25 dB(A)	-	-	393	492	591	693
	35 dB(A)	-	-	522	647	770	956
500	25 dB(A)	-	-	-	617	741	930
	35 dB(A)	-	-	-	802	956	1187

PRODUCT KEY

G	K	2	5	0	-	F	0	6	0	0	0	3	0	0
							Nominal length L (mm): From 100 to 750mm, per 50mm				Nominal height H (mm): From 100 to 550mm, per 50mm			
							F: Coated							

GK250

